



Fabryka Taśm Transporterowych
WOLBROM S.A.
32-340 Wolbrom, ul 1-go Maja 100
 tel. (032) 6497100 fax (032) 6497101

FTT WOLBROM®

Wolbrom 22.01.2010

CERTIFICATE OF QUALITY No. 21

1. Rubber fabric conveyor belt **EP 1250/4 W 6+2**
 according **DIN 22102**
 Belt number: **21 - 150 m**

2. Dimensions and physical parameters of belt

Requirements	Unit	Required	Obtained
Belt width	[mm]	900	898
Operating cover thickness	[mm]	6,0	6,4
Non operating cover thickness	[mm]	2,0	2,2
Tensile strength	[kN/m]	1250	1293
Elongation at load of 10% of nominal strength max.	[%]	2,5	0,6
Elongation at break	[%]	-	23,0
Separation resistance min.	[kN/m]		
- between the fabric plies		5,0	10,5
- of rubber covers form the core		4,5	8,1
Separation resistance change after ageing 70°x168h			
- between the fabric plies	%	- 25	-4,8
- rubber covers from the core	%	- 25	0,0
Electric resistance max	[Ω]	3,0x10 ⁸	2x10 ³

Signature and stamp of
 Quality Control

Specjalista ds. jakości

Konrad Danoś

Fabryka Taśm Transporterowych
WOLBROM S.A.
 32-340 Wolbrom, ul. 1 Maja 100
 tel. (032) 649-71-00, fax (032) 649-71-01
 NIP 637-10-01-853
 -18-